





**DIJKSTRA
PLASTICS**





« 4 P, ? P 8 ,

All Dijkstra Plastics products are suitable for all type of aqueous, acidic and alcoholic foods, foods which contain free fats at the surface and milk products.

£ ¨ ê P 8 ; È ? 8 [, g Ž Y ê ; 8 g [

All Dijkstra Plastics products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. The products are tested for 10 days at 60 °C which covers storage for above 6 months at room temperature and lower, including hot ll conditions and/ or heating up to 70 °C T 100 °C for maximum t = 120/2^((T-70)/10) minutes. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use. Before using the product make sure to read the speci c "Declaration of Compliance according 10/2011". Products used for infants, pharmaceutical purposes and repeated use may require additional testing.

M 8 - 4 ? ; Y < Ž ê ; ¨ Ž •

The material chosen has a very good heat resistance and the packaging is suitable for hot lling. Notably, plastic packaging becomes exible when subjected to hot lling temperatures and care must be taken in relation to stacking immediately after hot lling. This packaging must be tested by users and/or packers with the actual product before approval for use at high temperatures.

f g Â ? ; Y < Ž ê ; ¨ Ž •

Freezing conditions require special resins available on request. This packaging must be tested by the users and/or packers with the actual product before use at low temperatures.

} Ž - ê [g P < ; 8 ? 4 ê Ž ê ; Ž 8 • ; 8 •

The organoleptic properties can in uence the product in the package. It is therefore important to properly test the organoleptic properties before use.

« 4 P, ? P 8 ,

The compliance of the product to the technical speci cations in this data sheet is guaranteed for 12 months after the date of delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low or very high temperatures over a longer period.

£ ¨ ê P 8 ; È ? 8 [, g Ž Y ê ; 8 g [

Deviations in the product speci cations in this data sheet of 0,025% or less (i.e. 25 items per 100,000 pcs) are considered acceptable in the industry and therefore cannot be considered as a defect. Also, please refer to the General Sales and Delivery conditions in force at the time of delivery.

